

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

### Section 1. Identification of the substance or the mixture and of the supplier

#### 1.1 Product Identifier

**Product identifier:** Tekstat Floor Finish FF 5510 (FF5500)

**Other identifiers:** None

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product uses:** Antistatic floor polish

#### 1.3 Details of the supplier of the safety data sheet

**Company name:** Teknis Ltd

**Company address:** Unit 5, Valley Farm Estate  
Station Road  
Meldreth  
Herts  
SG8 6JP

**Contact:** Davina Biswell

**E-Mail address:** davina@teknis.co.uk

**Company phone:** + 44 (0) 1763 261690

#### 1.4 Emergency telephone number

**Emergency phone:** + 44 (0) 1763 261690

### Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

**Class and category of danger:** Skin Corrosion / Irritation Category 2  
Eye Damage / Irritation Category 2  
Toxic to Reproduction Category 2  
Hazardous to the Aquatic Environment - Long-term Hazard Category 2  
H315, Causes skin irritation.  
H319, Causes serious eye irritation.  
H361, Suspected of damaging fertility or the unborn child (exposure route).  
H411, Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Signal word:** Warning

**Hazard statements:** H315, Causes skin irritation.  
H319, Causes serious eye irritation.  
H361, Suspected of damaging fertility or the unborn child (exposure route).  
H411, Toxic to aquatic life with long lasting effects.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

**Precautionary statements:**

P202, Do not handle until all safety precautions have been read and understood.  
 P264, Wash hands and other contacted skin thoroughly after handling.  
 P273, Avoid release to the environment.  
 P280, Wear protective gloves/eye protection/face protection.  
 P302/352, IF ON SKIN: Wash with plenty of soap and water.  
 P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308/313, IF exposed or concerned: Get medical advice/attention.  
 P332/313, If skin irritation occurs: Get medical advice/attention.  
 P337/313, If eye irritation persists: Get medical advice/attention.  
 P362, Take off contaminated clothing and wash before reuse.  
 P391, Collect spillage.  
 P405, Store locked up.  
 P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

**Pictograms:**



**Other hazards:** None

### Section 3. Composition / information on ingredients

#### 3.2 Mixtures

**Contains:**

Name	CAS	EC	%	GHS Classification
TEK FF 5500			50-100%	SCI 2-EDI 2-REP 2-EH C2;H315-H319-H361-H411

**Substances with Community workplace exposure limits, not listed above:**

Not Applicable

### Section 4. First-aid measures

#### 4.1 Description of first aid measures

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

### 4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child (exposure route).

### 4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

### 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

### 5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

### 6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

### 6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

### 6.4 Reference to other sections:

Also refer to sections 8 and 13.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

### 7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed.

Specific end use(s):

Antistatic product: Use in accordance with good manufacturing and industrial hygiene practices.

### Section 8. Exposure controls/personal protection

#### 8.1 Control parameters

Workplace exposure limits: Not Applicable

#### 8.2 Exposure Controls

##### Eye / Skin Protection

Wear protective gloves/eye protection/face protection

##### Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

### Section 9. Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	White liquid
<b>Odour:</b>	Mild
<b>pH:</b>	8.0 – 9.0
<b>Initial boiling point / range:</b>	100°C / 212°F
<b>Flash point:</b>	non flammable
<b>Vapour pressure:</b>	Not determined
<b>Relative density:</b>	Not determined
<b>Solubility(ies):</b>	infinitely miscible in water
<b>9.2 Other information:</b>	None available

### Section 10. Stability and reactivity

#### 10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

### 10.2 Chemical stability:

Good stability under normal storage conditions.

### 10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

### 10.4 Conditions to avoid:

Avoid extreme heat.

### 10.5 Incompatible materials:

None known based on information provided.

### 10.6 Hazardous decomposition products:

Not expected.

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child (exposure route).

**Assumed Toxicity Value (LD50 or ATE) for Acute Oral Toxicity:** Not Applicable

**Assumed Toxicity Value (LD50 or ATE) for Acute Dermal Toxicity:** Not Applicable

**Assumed Toxicity Value (LC50 or ATE) for Acute Inhalation Toxicity:** Not Available

**Inhalation Route:** Not Available

### Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

## Section 12. Ecological information

### 12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability:** Not available

**12.3 Bioaccumulative potential:** Not available

**12.4 Mobility in soil:** Not available

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)

**Version:** 1

### 12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6 Other adverse effects:** Not available

### Section 13. Disposal considerations

#### 13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### Section 14. Transport information

**14.1 UN number:** UN3082

**14.2 UN Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TEK FF 5500)

**14.3 Transport hazard class(es):** 9

**Sub Risk:** -

**14.4. Packing Group:** III

**14.5 Environmental hazards:** This is an environmentally hazardous substance.

**14.6 Special precautions for user:** None additional

**14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:**

Not applicable

### Section 15. Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None additional

#### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

### Section 16. Other information

**Concentration % Limits:** EH C2=25.00% EH C3=2.50% EH C4=25.00% SCI 2=10.00% SCI3=1.00000000% EDI 2A=10.00% REP 2=3.00%

**Total Fractional Values:** EH C2=4.00 EH C3=40.00 EH C4=4.00 SCI 2=10.00 SCI 3=100.00 EDI 2A=10.00 REP 2=33.33

#### Key to revisions:

Not applicable

## SAFETY DATA SHEET

In accordance with UN GHS latest edition

**Product:** Tekstat Floor Finish FF5510 (FF5500)**Version:** 1**Key to abbreviations:**

Abbreviation	Meaning
EDI 2	Eye Damage / Irritation Category 2
EH C2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child (exposure route).
H411	Toxic to aquatic life with long lasting effects.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash hands and other contacted skin thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308/313	IF exposed or concerned: Get medical advice/attention.
P332/313	If skin irritation occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
REP 2	Toxic to Reproduction Category 2
SCI 2	Skin Corrosion / Irritation Category 2

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.